

DES PRODUITS

Maison / Des Produits / Zone De Sécurité Cansafe / Souffleur Axial En Plastique Antidéflagrant, 115 VAC, 1/3 HP, 2,2 A, 3250 Tr/Min

D'ARTICLE RECHERCHE

Rechercher des produits

RETOUR AUX PRODUITS

DE PRODUITS CATÉGORIES

- Équipement de protection individuelle
 - Vêtements jetables et résistants aux produits chimiques
 - Ergonomie
 - Protection des yeux et du visage
 - Protection contre les chutes
 - Chaussures Et Accessoires
 - Vêtements résistants aux flammes et aux arcs électriques
 - Protection des mains et des bras
 - Protection de la tête
 - Protection auditive
 - High-Visibility And Traffic Clothing
 - Rainwear
 - Respiratory Protection
 - Welding PPE
 - Workwear
 - Disp/chem Resistant Clothing
 - Fr And Arc Flash Clothing
 - High Vis And Traffic Clothing
- Restoration and Abatement
 - Jobsite Safety
 - MRO Supplies
 - Janitorial Supplies
 - Clearance Items (1)



Numéro d'article CANS9539-12EX

SOUFFLEUR AXIAL EN PLASTIQUE ANTIDÉFLAGRANT, 115 VAC, 1/3 HP, 2,2 A, 3250 TR/MIN

MARQUE : Cansafe Safety Zone

CATÉGORIE : Sécurité sur le chantier - Espace confiné - Ventilation antidéflagrante

TAILLE DE L'UNITÉ : Chaque

DISPONIBILITÉ : sélectionnez l'emplacement

\$3,539.94

Taille de l'unité	Tarifcation
Chacun(1) :	\$3539.94

1

AJOUTER AU PANIER

AVAILABILITY

DESCRIPTION

ALLEGRO® portable blower is ideally suited for large confined spaces in statically conductive environments. This blower delivers both positive and negative airflow and is perfect for confined spaces such as paper mills, tank purging or utility sites. It can also be used as an inline booster blower.

Features

- Lightweight-, corrosion-, UV- and chemical-resistant polyethylene
- ?safety
- orange
- ? colored housing
- Durable construction design
- Super quiet
- Bottom enclosure to protect electrical components
- Carry handle molded into blower
- Stackable

Attributes	
Brand	ALLEGRO
Type	Axial Explosion-proof
Width	21 in
Length	17 in
Height	21 in
Color	Orange
Power Rating	1/3 HP
Voltage Rating	115 VAC
Cord Length	25 ft
Frequency Rating	60 HZ
Speed Rating	3250 rpm
Current Rating	2.2 A
Standards	CSA

RESOURCES

- About
- Products
- News
- Careers
- HazSafeID Login
- Contact
- Credit Application
- Privacy Policy
- Accessibility
- End to End Pandemic Program

SAFETY SERVICES

- eStock Inventory Management
- Respiratory Fit Testing
- Equipment Rentals and Leasing
- Equipment Inspection
- Equipment Service & Repair
- DOP/PAO Testing

SAFETY TRAINING

- Health and Safety Training
- IICRC Training
- Infrared Camera Training
- Training Schedule

MY ACCOUNT

- Sign In
- Register
- Viewcart
- Check Out

GET IN TOUCH

- For Sales & Service, call (877) 747-7117
- For Corporate & Purchasing, call (800) 434-7065
- Email us at: connect@hazmasters.com

FOLLOW US @



